



CENTRE FOR DEVELOPMENT STUDIES

ULLOOR, THIRUVANANTHAPURAM

PHONE- 0471 2774255, 2774200

September 30, 2021

TENDER NOTICE

The CDS invites sealed bids for re tarring the campus road. Bids should be submitted to the Registrar, Centre for Development Studies, Thiruvananthapuram on or before 20th October 2021 by 10.00 a.m. The details are available at the Estate and Engineering section of the Centre and the CDS website (www.cds.edu).

Registrar



CENTRE FOR DEVELOPMENT STUDIES

ULLOOR, THIRUVANANTHAPURAM

PHONE- 0471 2774255, 2774200

TENDER NUMBER - 02/2021-22

NAME OF WORK - Re tarring campus road at Centre for Development Studies.

LAST DATE OF TENDER FORM ISSUE - 18/10/2021 4.00 PM

LAST DATE OF SUBMITTING TENDER - 20/10/2021 UPTO 10.00 AM

OPENING OF TENDER - 20/10/2021 - 10.30 AM

PROBABLE AMOUNT OF CONTRACT - RS.5,45,000.00

E.M.D: **RS. 5,500.00** (*DD in favour of Registrar, Centre for Development Studies*)

TIME OF COMPLETION OF WORK – ON OR BEFORE 31st December 2021.

DESCRIPTION OF WORK: **please see Annexure I**

AMOUNT QUOTED (In figure) :

(In words) :

Name and Address:

.....

.....

Signature

Annexure I

Item No.	Description	Area (Sq.M)	Rate /sqm	AMOUNT
1.	75.5.2.1pb Tack Coat - With Packed Bitumen Rates Providing and applying tack coat with Bitumen emulsion (RS-1) using emulsion distributor at the rate of 0.20 to 0.25 kg per sqm on the prepared bituminous surface cleaned with Hydraulic broom as per Technical Specification Clause 503.	1838.55		
2.	75.5.5.B.2pb Modified Penetration Macadam 75 mm thick using Bitumen S-65 - Packed Bitumen Rates Construction of penetration macadam over prepared base by providing a layer of compacted crushed coarse aggregate using chips spreader with alternate applications of bituminous binder and key aggregates and rolling with a three wheel 80-100 kN static roller to achieve the desired degree of compaction as per Technical Specification Clause 506.	220		
3.	75.5.9.1.2pb 20mm thick Open-Graded Premix Carpet using Bituminous (penetration grade/modified bitumen) Binder - Bitumen S-65 - Packed Bitumen Rates Providing, laying and rolling of open-graded premix carpet of 20 mm thickness composed of 13.2 mm to 5.6 mm aggregates either using penetration grade bitumen or emulsion to required line, grade and level to serve as wearing course on a previously prepared base, including mixing in a suitable plant, laying and rolling with a three wheel 80-100 kN static roller capacity, finished to required level and grades to be followed by seal coat of either Type A or Type B or Type C as per Technical Specification Clause 508. Case - I By Manual Means	1838.55		
4.	75.5.12.A.3.2pb Seal Coat - Manual Means - Type C - Bitumen S-65 - Packed Bitumen Rates Providing and laying seal coat sealing the voids in a bituminous surface laid to the specified levels, grade and cross fall using Type A, Type B and Type C as per Technical Specification Clause 510 A. By Manual Means Case III : Type C (II)Bitumen (S-65)	1838.55		

TOTAL AMOUNT